

SteelCentral Product Family Specifications

Riverbed® SteelCentral™ AppResponse Solutions

Model Specifications

SteelCentral AppResponse xx80 Appliances

Model	2180	4180	8180		Storage Units (for Model 8180)	
			8180	8180 Plus	48 TB Storage Unit	120 TB Storage Unit
Product SKU	SCAN-02180	SCAN-04180	SCAN-08180		SCAN-SU-4	SCAN-SU-10
Storage	12 TB raw 10 TB usable	48 TB raw 40 TB usable (RAID 0)	None		48 TB	120 TB
Supported Storage Units	N / A		1	Up to 16 ⁵	N / A	
Maximum Storage Capacity	12 TB raw 10 TB usable	48 TB raw 40 TB usable (RAID 0)	120 TB	1.92 PB	48 TB	120 TB
Storage Disk Capacity ^{1,2}	2 x 6 TB	8 x 6 TB	N / A		12 x 4 TB	12 x 10 TB
Storage Disk Redundancy	SW RAID level 0	HW RAID 0 (default), 5, 6	N / A		HW RAID 0 (default), 5, 6 ⁶	
Data Encryption at Rest	N / A		N / A		Yes	
System and Data Capacity ^{3,4}	4 TB usable (2 x 4 TB)	8 TB usable (4 x 4 TB)	16 TB usable (8 x 4 TB)		N / A	
System and Data Disk Redundancy	Yes (RAID 10)				N / A	
Operating System	Customized Linux-based OS				N / A	
RAM (GB)	32	64	128		N / A	
Available Network Interface Card Slots	1	2		N / A		
Available Capture Ports	One of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber	Up to two of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber - 4 x 10 GbE Fiber	Up to two of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber - 4 x 10 GbE Fiber Or one of the following NICs: - 2 x 40 GbE Fiber	Up to two of the following NICs: - 4 x 1 GbE Copper - 4 x 1 GbE Fiber - 2 x 10 GbE Fiber - 4 x 10 GbE Fiber Or one of the following NICs: - 2 x 40 GbE Fiber - 2 x 100 GbE Fiber	N / A	
Management Port (10/100/1000 RJ45)	2		2		N / A	

1. Raw Disk Capacity. 1 TB = 10¹² Bytes. It does not take into account disk formatting or RAID overhead.
 2. Storage Disks store packets, and in addition can be configured to store performance metrics data.
 3. Raw Disk Capacity. 1 TB = 10¹² Bytes. It does not take into account disk formatting or OS usage.
 4. System and Data Disks store performance metrics data in addition to Operating System data.
 5. All Storage Units on an individual model 8180 must be of the same capacity. With no Storage Units attached, available storage is limited to system and data capacity.
 6. RAID 6 is not an option for the model 8180 when metrics priority storage mode is selected.
 7. Supported inserts - 100 G Fibre ports are available with SR and LR QSFP28 inserts. 40 G Fibre ports are available with SR4, LR4, and LM4 QSFP inserts. 10 G Fibre ports are available with SR and LR SFP+ inserts (LC connectors). 1 G Fibre ports are available with SX and LX SFP inserts (LC connectors).

SteelCentral AppResponse Solutions

Power and Physical Specifications

SteelCentral AppResponse

Model	2180	4180	8180		Storage Units (for Model 8180)	
			8180	8180 Plus	48 TB Storage Unit	120 TB Storage Unit
Product SKU	SCAN-02180	SCAN-04180	SCAN-08180		SCAN-SU-4	SCAN-SU-10
Dual Power Supplies (redundant)	✓					
Power [Watts] (typical)	132	308	408		150	170
BTU	450	1,050	1,391		512	580
Line Power Requirement	100V to 240V 50Hz to 60Hz	100V to 127V and 200V to 240V 50Hz to 60Hz			100V to 240V 50Hz to 60Hz	
Operating Temperature ¹	10 to 35°C (50 to 95°F)					
Humidity (shipping)	50 to 90%, non-condensing with a maximum wet bulb of 28°C (at temperatures from 25 to 35°C)					
Rack Size	1 U	2 U				
System Dimensions (LxWxH) ²	645 mm (L) X 436 mm (W) X 43.6 mm (H) 25.4" (L) X 17.2" (W) X 1.72" (H)	700 mm (L) X 440 mm (W) X 87 mm (H) 27.56" (L) X 17.32" (W) X 3.43" (H)			647 mm (L) X 437 mm (W) X 89 mm (H) 25.5" (L) X 17.2" (W) X 3.5" (H)	
Packaging Dimensions (LxWxH) ³	914.4 mm (L) X 609.6 mm (W) X 304.8 mm (H) 36" (L) X 24" (W) X 12" (H)				876 mm (L) X 678 mm (W) X 290 mm (H) 34.5" (L) X 26.7" (W) X 11.4" (H)	
Max Weight (without packaging) ⁴	47 pounds	68 pounds	62 pounds		75 pounds	
Rail Information	Mounting Rail Kit Included. Orderable Spare Part Number: RMK-4-1U	Mounting Rail Kit Included. Orderable Spare Part Number: RMK-4-2U		Mounting Rail Kit Included. Orderable Spare Part Number: RMK-4-JBOD		
RoHS Compliant	✓					

1. Operating altitude up to 10,000 feet except in China 6,562 feet (2,000m).

2. Length is without bezel or cables.

3. Packaging dimensions do not include the pallet on which the unit might be shipped.

4. Weight does not include rails and front bezel

Note: The availability, export or re-export of these products or specific features are subject to the export laws and regulations of the U.S. and the laws and regulations of any applicable foreign agency or authority.

SteelCentral AppResponse Solutions

Model Specifications

SteelCentral AppResponse Virtual					SteelCentral AppResponse Cloud	
Model	VSCAN-00100	VSCAN-00500	VSCAN-02000	VSCAN-FLOW	VSCAN-AWS-SUB-010	VSCAN-AZR-SUB-010
Secondary Storage	Up to 100 GB	Up to 2 TB	Up to 8 TB	Up to 100 GB	16 GB to 8 TB	16 GB to 8 TB
Hypervisor	VMware ESXi 5.5, 6.0 and 6.5				AWS EC2	Azure
vCPU	4				8 (t2.2xlarge)	8 (standard_B8ms)
Memory	8 GB				32 GiB (t2.2xlarge)	32 GiB (standard_B8ms)
System Disk Space	100 GB				2 TB	
Capture Ports	Up to 8				1 (shared mgmt/capture port)	
Management Ports	2				1 (shared mgmt/capture port)	

Riverbed® SteelCentral™ NetProfiler Solutions

Product Specifications

Model	SteelCentral NetProfiler Supports up to 30 million deduplicated flows per minute ⁶		
	SCNP-04280 ^{5,6}	SCNP-04280 ^{5,6} Expansion	
	SCNP-04280	SCNP-04280-EX	SCNP-04280-DP
De-Duplicated Flow Capacity (flows per minute) ¹	100,000 to 1,500,000	100,000 to 1,500,000	N / A
Raw Flow Capacity (flows per minute) ⁸	7.5M	7.5M	N / A
Raw Flow Capacity with Advanced Security Module (FPM) ⁸	7.5M	7.5M	N / A
Raw Disk Capacity ²	52 TB	52 TB	4 TB
Usable Disk Capacity ⁹	20 TB	20 TB	N / A
Optional 10 GB LAN Support ⁷	N / A	N / A	✓
Optional Fibre Channel SAN Support ⁷	✓	✓	N / A
RAID	RAID 1 / RAID 10	RAID 1 / RAID 10	RAID 1
Hard Disk Drives	8	8	2
Solid State Drives	6	6	N / A
RAM	256 GB	256 GB	96 GB
Serial Port (DB-9)		✓	
Primary Cascade Management Port ⁴ (10/100/1000 RJ45)		✓	
Flow as Data Source ¹⁰		N / A	

- Flow capacity can be expanded up to the amount listed.
- Raw Disk Capacity does not take into account disk formatting, RAID overhead, software installation, or OS usage.
- Each Flow Gateway model can report to up to two NetProfilers and forward flow to five third-party flow collectors.
- SCAN-04280-xxx and SCNP-04280-EXP equipped with RAID 10 (48 TB) and RAID10 (3.8 TB SSDs).
- Up to 19 SCNP-04280-EXP expansion modules may be added to each SCNP-04280 system. Each additional SCNP-04280-EXP enables up to 1.5M de-duplicated FPM. Maximum of 30M de-duplicated flows/min supported. SCNP-04280-DP is required with addition of sixth SCNP-04280-EXP after more than 10M FPM.
- Requires compatible SFPs.
- A flow reported by a single network interface is a raw flow. NetProfiler will de-duplicate up to 10 individual interfaces reporting the same flow into 1 de-duplicated flow.
- Disk capacity available for storage of data.
- Accepts NetFlow (V1, V5, V7, and V9), Enhanced NetFlow, IPFIX, cFlow, Cisco NBAR and NBAR2, Cisco MediaNet, Cisco ASA NSEL, Citrix AppFlow, sFlow V2 and V5, J-Flow, Packeteer FDR, Palo Alto Networks, SteelCentral Flow from Riverbed appliances, and AWS VPS Flows.

SteelCentral NetProfiler Solutions

Power and Physical Specifications

Model	SteelCentral NetProfiler		
	SCNP-04280	SCNP-04280 Expansion	
	SCNP-04280	SCNP-04280-EX	SCNP-04280-DP
Dual Power Supplies (redundant)	✓	✓	✓
Power [Watts] (typical)	268		232
BTU	913		791
Operating Temperature ¹	10 to 35°C (50 to 95°F)		
Relative Humidity (shipping)	50 to 90%, non-condensing with a maximum wet bulb of 28°C (at temperatures from 25 to 35°C)		
Rack Size	2 U	2 U	1 U
System Dimensions (LxWxH) ²	700 mm (L) x 440 mm (W) x 87 mm (H) 27.56" (L) x 17.32" (W) x 3.43" (H)		645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)
Packaging Dimensions (LxWxH) ³	914.4 mm (L) x 609.6 mm (W) x 304.8 mm (H) 36" (L) x 24" (W) x 12" (H)		645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)
Weight (without packaging) ⁴	61 lb	61 lb	44 lb
Rail Information	Mounting rail kit included. Orderable spare part number: RMK-4-2 U		Mounting rail kit included. Orderable spare part number: RMK-4-1 U
RoHS Compliant	✓	✓	

1. Operating altitude up to 10,000 feet except in China 6,562 feet (2,000m).
2. Length is without bezel or cables.

3. Packaging dimensions do not include the pallet on which the unit might be shipped.
4. Weight does not include rails and front bezel.

SteelCentral NetProfiler Virtual

System Requirements

SteelCentral NetProfiler Virtual Base / Expansion Supports up to 30 million deduplicated flows per minute¹¹

Model	SCNP-VE / SCNP-VE-EXP				
Deduplicated Flow Capacity (flows per minute)	Up to 10,000	20,000 to 100,000	110,000 to 500,000	510,000 to 1,000,000	1,010,000 to 1,500,000
Raw Flow Capacity (flows per minute)	Up to 50,000	100,000 to 500,000	550,000 to 2,500,000	2,550,000 to 5,000,000	5,050,000 to 7,500,000
Hypervisor	VMware ESXi 6.5 and 6.7				
vCPU	4 CPUs minimum	4 CPUs minimum / 12 CPUs recommended	8 CPUs minimum / 16 CPUs recommended	12 CPUs minimum/ 24 CPUs recommended	16 CPUs minimum / 32 CPUs recommended
	2.6 GHz recommended				
RAM	8 GB minimum / 32 GB recommended	16 GB minimum / 64 GB recommended	32 GB minimum / 96 GB recommended	64 GB minimum / 128 GB recommended	96 GB minimum / 256 GB recommended
System Disk Space	250 GB				
Flow Storage Space	250 GB minimum / 50 TB maximum per BASE or EXP				
Flow Cache Space (optional)	Optional, 250 GB minimum / 5 TB maximum per BASE or EXP				
Flow Storage IOPS (primary data storage)	150 minimum / 500+ recommended	500 minimum / 2,000+ recommended	1,500 minimum / 4,000+ recommended	2,000 minimum / 5,000+ recommended	
Flow Cache IOPS (optional) ¹²	300 minimum / 1,000+ recommended	1,000 minimum / 4,000+ recommended	3,000 minimum / 8,000+ recommended	4,000 minimum / 9,000+ recommended	

9. Operating altitude up to 10,000 feet
10. Length is without bezel, rack ears, cables.
11. Up to 19 SCNP-EXP-VE expansion modules may be added to each SCNP-BASE-VE system. Each additional SCNP-EXP-VE enables up to 1.5M de-duplicated FPM. A maximum of 30 million de-duplicated flows/min is supported. SCNP-DP-VE is required after more than 10 million FPM.

12. The optional Flow Cache disk can be used to store the most recently collected data on a faster storage tier to make reporting on the more recent data faster. We recommend provisioning SSD storage which is 10% the size of the primary flow storage.

Note: The availability, export or re-export of these products or specific features are subject to the export laws and regulations of the U.S. and the laws and regulations of any applicable foreign agency or authority.

SteelCentral NetProfiler Virtual

System Requirement

SteelCentral NetProfiler Virtual Dispatcher

Model	SCNP-VE-DP
Deduplicated Flow Capacity (flows per minute)	0 to 30,000,000
Raw Flow Capacity (flows per minute)	0 to 150,000,000
Flow Capacity beyond which DP is required	10,000,000
Hypervisor	VMware ESXi 6.5 and 6.7
vCPU	16 CPUs minimum / 24 CPUs recommended 2.1 GHz minimum / 2.6 GHz recommended
RAM	32 GB minimum / 64 GB recommended
System Disk Space	250 GB

SteelCentral NetProfiler Cloud

Model Specifications

SteelCentral NetProfiler Cloud Base/Expansion

Model	SCNP-VE / SCNP-VE-EXP			
Deduplicated Flow Capacity (flows per minute)	Up to 100,00	110,000 to 375,000	385,000 to 750,000	760,000 to 1,500,000
Raw Flow Capacity (flows per minute)	Up to 500,000	550,000 to 1,875,000	1,925,000 to 3,750,000	3,800,000 to 7,500,000
AWS Instance Type	r4.xlarge	r4.2xlarge	r4.4xlarge	r4.8xlarge
Azure Instance Type	E4s_v3	E8s_v3	E16s_v3	E32s_v3
System Disk Space	250 GB			
System Disk Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Flow Storage Cache (optional)	250 GB minimum / 5 TB maximum per BASE or EXP			
Flow Storage Cache Type	AWS (GP2 SSD minimum/ io1 SSD recommended), Azure (Premium SSD recommended)			
Flow Storage Primary	256 GB minimum	1 TB minimum	2T minimum	
	50 TB maximum ¹			
Flow Storage Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Management Ports	1			

1. While NetProfiler supports 50 TB maximum, disk volume size is limited to 16T on AWS and 32T on Azure.

SteelCentral NetProfiler Cloud

Model Specifications

SteelCentral NetProfiler Cloud Dispatcher

Model	SCNP-VE-DP	
Deduplicated Flow Capacity (flows per minute)	0 to 10,000,000	10,010,000 to 30,000,000
Raw Flow Capacity (flows per minute)	0 to 50,000,000	50,050,000 to 150,000,000
AWS Instance Type	r4.8xlarge	
Azure Instance Type	E32s_v3	E48s_v3
System Disk Type	250GB	
System Disk Space	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)	

Riverbed® SteelCentral™ Flow Gateway

Product Specifications

Model	SteelCentral Flow Gateway
	SCFG-02280 Series
De-Duplicated Flow Capacity (flows per minute) ¹	100,000 to 6,000,000
Raw Flow Capacity (flows per minute) ⁸	40M
Raw Flow Capacity with Advanced Security Module (FPM) ⁸	20M
Raw Disk Capacity ²	4 TB
Usable Disk Capacity ⁹	1 TB
Optional 10 GB LAN Support ⁷	✓
Optional Fibre Channel SAN Support ⁷	N / A
RAID	RAID 1
Hard Disk Drives	2
Solid State Drives	N / A
RAM	64 GB
Serial Port (DB-9)	✓
Primary Cascade Management Port ⁴ (10/100/1000 RJ45)	✓
Flow as Data Source ¹⁰	✓

SteelCentral Flow Gateway

Power and Physical Specifications

Model	SteelCentral Flow Gateway
	SCFG-02280 Series
Dual Power Supplies (redundant)	✓
Power [Watts] (typical)	200
BTU	682
Operating Temperature ¹	10 to 35°C (50 to 95°F)
Relative Humidity (shipping)	50 to 90%, non-condensing with a maximum wet bulb of 28°C (at temperatures from 25 to 35°C)
Rack Size	1 U
System Dimensions (LxWxH) ²	645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)
Packaging Dimensions (LxWxH) ³	645 mm (L) x 436 mm (W) x 43.6 mm (H) 25.4" (L) x 17.2" (W) x 1.72" (H)
Weight (without packaging) ⁴	43 lb
Rail Information	Mounting rail kit included. Orderable spare part number: RMK-4-1 U
RoHS Compliant	✓

- Flow capacity can be expanded up to the amount listed.
- Raw Disk Capacity does not take into account disk formatting, RAID overhead, software installation, or OS usage.
- Each Flow Gateway model can report to up to two NetProfilers and forward flow to two third-party flow collectors.
- SCAN-04280-xxx and SCNP-04280-EXP equipped with RAID 10 (48 TB) and RAID10 (3.8 TB SSDs).
- Up to 19 SCNP-04280-EXP expansion modules may be added to each SCNP-04280 system. Each additional SCNP-04280-EXP enables up to 1.5M de-duplicated FPM. Maximum of 30M de-duplicated flows/min supported. SCNP-04280-DP is required with addition of sixth SCNP-04280-EXP after more than 10M FPM.
- Requires compatible SFPs.
- A flow reported by a single network interface is a raw flow. NetProfiler will de-duplicate up to 10 individual interfaces reporting the same flow into 1 de-duplicated flow.
- Disk capacity available for storage of data.
- Accepts NetFlow (V1, V5, V7, and V9), Enhanced NetFlow, IPFIX, cFlow, Cisco NBAR and NBAR2, Cisco MediaNet, Cisco ASA NSEL, Citrix AppFlow, sFlow V2 and V5, J-Flow, Packeteer FDR, Palo Alto Networks, SteelCentral Flow from Riverbed appliances, and AWS VPS Flows.

SteelCentral Flow Gateway Virtual

System Requirements

SteelCentral Flow Gateway Virtual

Model	SCFG-VE					
Deduplicated Flow Capacity (flows per minute)	Up to 10,000	20,000 to 100,000	110,000 to 1,000,000	1,010,000 to 2,000,000	2,010,000 to 4,000,000	4,010,000 to 6,000,000
Raw Flow Capacity (flows per minute)	Up to 50,000	100,000 to 500,000	550,000 to 5,000,000	5,050,000 to 10,000,000	10,050,000 to 20,000,000	20,050,000 to 30,000,000
Hypervisor	VMware ESXi 6.5 and 6.7					
vCPU	2 CPUs recommended	2 CPUs minimum / 4 CPUs recommended	4 CPUs minimum / 6 CPUs recommended	6 CPUs minimum / 8 CPUs recommended	8 CPUs minimum / 12 CPUs recommended	12 CPUs minimum / 18 CPUs recommended
	2.6 GHz recommended					
RAM	2 GB minimum / 4 GB recommended	4 GB minimum / 8 GB recommended	8 GB minimum / 16 GB recommended	16 GB minimum / 24 GB recommended	24 GB minimum / 32 GB recommended	32 GB minimum / 48 GB recommended
System Disk Space	250 GB					
Flow Storage	250 GB minimum / 2 TB maximum					
Management Ports	2					

SteelCentral Flow Gateway Virtual

System Requirements

SteelCentral Flow Gateway Virtual with Advanced Security Module

Model	SCFG-VE					
Deduplicated Flow Capacity (flows per minute)	Up to 10,000	20,000 to 100,000	110,000 to 1,000,000	1,010,000 to 2,000,000	2,010,000 to 4,000,000	4,010,000 to 6,000,000
Raw Flow Capacity (flows per minute)	Up to 50,000	100,000 to 500,000	550,000 to 5,000,000	5,050,000 to 10,000,000	10,050,000 to 20,000,000	Up to 20,000,000
Hypervisor	VMware ESXi 6.5 and 6.7					
vCPU	4 CPUs recommended	4 CPUs minimum / 6 CPUs recommended	6 CPUs minimum / 8 CPUs recommended	8 CPUs minimum / 12 CPUs recommended	12 CPUs minimum / 16 CPUs recommended	16 CPUs minimum / 24 CPUs recommended
	2.6 GHz recommended					
RAM	2 GB minimum / 4 GB recommended	4 GB minimum / 8 GB recommended	8 GB minimum / 16 GB recommended	16 GB minimum / 24 GB recommended	24 GB minimum / 32 GB recommended	32 GB minimum / 48 GB recommended
System Disk Space	250 GB					
Flow Storage	500 GB					
Management Ports	2					

SteelCentral Flow Gateway Cloud

Model Specifications

Model	SCFG-VE			
Deduplicated Flow Capacity (flows per minute)	Up to 100,000	110,000 to 1,000,000	1,010,000 to 3,000,000	3,010,000 to 6,000,000
Raw Flow Capacity (flows per minute)	Up to 500,000	550,000 to 5,000,000	5,050,000 to 15,000,000	15,050,000 to 30,000,000
AWS Instance Type	r4.large or m4.large	r4.xlarge or m4.xlarge	r4.2xlarge or m4.2xlarge	r4.4xlarge or m4.4xlarge
Azure Instance Type	E2s_v3 or D2s_v3	E4s_v3 or D4s_v3	E8s_v3 or D8s_v3	E16s_v3 or D16s_v3
System Disk Space	250 GB			
System Disk Type	AWS (GP2 SSD recommended), Azure (Premium SSD)			
Flow Storage	250 GB minimum / 2 TB maximum			
Flow Storage Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Management Ports	Up to 2			

SteelCentral Flow Gateway Cloud

Model Specifications

SteelCentral Flow Gateway Cloud with Advanced Security Module

Model	SCFG-VE			
Deduplicated Flow Capacity (flows per minute)	Up to 100,000	110,000 to 1,000,000	1,010,000 to 3,000,000	3,010,000 to 6,000,000
Raw Flow Capacity (flows per minute)	Up to 500,000	550,000 to 5,000,000	5,050,000 to 10,000,000	Up to 10,000,000
AWS Instance Type	r4.xlarge	r4.2xlarge	r4.4xlarge	r4.8xlarge
Azure Instance Type	E4s_v3	E8s_v3	E16s_v3	E32s_v3
System Disk Space	250 GB			
System Disk Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Flow Storage	250 GB minimum / 2 TB maximum			
Flow Storage Type	AWS (GP2 SSD recommended), Azure (Premium SSD recommended)			
Management Ports	Up to 2			

Riverbed® SteelCentral™ NetIM

Model Specifications

SteelCentral NetIM Manager¹ (Virtual and Cloud Images)

Devices ¹	2.5K	5K	10K	15K	20K	25K	30K
Interface Count ²	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	50K	100K	200K	300K	400K	500K	600K
vCPUs	4		6	8		10	
Memory	16 GB		24 GB	32 GB	40 GB	48 GB	56 GB
OS Storage	75 GB						
App Storage	1 TB	2 TB				3 TB	
Hypervisor ^{5,6}	VMware ESXi 6.5 and 6.7						
Managers	1						

SteelCentral NetIM

Model Specifications

SteelCentral NetIM Data Manager² (Virtual and Cloud Images)

Devices	2.5K	5K	10K	15K	20K	25K	30K
Interface Count	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	50K	100K	200K	300K	400K	500K	600K
vCPUs	N / A	N / A	4				
Memory	N / A	N / A	16 GB				
OS Storage	N / A	N / A	75 GB				
App Storage	N / A	N / A	2 TB				
Hypervisor ^{5,6}	VMware ESXi 6.5 and 6.7						
Data Managers ³	0		1	2		3	

SteelCentral NetIM

Model Specifications

SteelCentral NetIM Worker (Virtual and Cloud Images)

Devices	2.5K	5K	10K	15K	20K	25K	30K
Interface Count	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	50K	100K	200K	300K	400K	500K	600K
vCPUs	4						
Memory	16 GB						
OS Storage	75 GB						
App Storage	100 GB						
Hypervisor ^{5,6}	VMware ESXi 6.5 and 6.7						
Workers ⁴	1	2	4	6	8	10	12

SteelCentral NetIM

Model Specifications

SteelCentral NetIM Core (Virtual and Cloud Images)

Devices	2.5K	5K	10K	15K	20K	25K	30K
Interface Count	100K	200K	400K	600K	800K	1M	1.2M
Polled Interface Count	50K	100K	200K	300K	400K	500K	600K
vCPUs	4	6	8				
Memory	16 GB	32 GB	48 GB	64 GB	80 GB	96 GB	112 GB
OS Storage	75 GB						
App Storage	100 GB	200 GB	250 GB	300 GB	350 GB	400 GB	450 GB
Hypervisor ^{5,6}	VMware ESXi 6.5 and 6.7						
Core	1	1	1	1	1	1	1

1. Manager and Data Manager Application Storage requirements are primarily dependent on metric retention and roll-up settings. For proof-of-concepts, the default App Storage of 100 GB may be enough if metric retention settings are reduced from the system defaults.
2. Assuming 5-minute polling and minimal latency between workers and polled elements. If CoS metrics are polled, each CoS definition applied to a polled interface counts as an additional logical interface, thereby increasing the overall polled interface count).
3. Write and query performance may improve with additional Data Manager nodes

4. Use the netimsh "scale" command on the Manager to scale the poller and alerting services to equal the number of deployed Workers. See the NetIM Installation Guide or Upgrade Guide for instructions.
5. VMotion should be disabled for all NetIM VMs.
6. ESXi servers must be geographically collocated in the same data center for minimum latency.

Riverbed® SteelCentral™ Portal

Model Specifications

SteelCentral Portal³

Product SKU	SCPRTL-FNDTN
vCPUs ¹	4
Memory	16 GB
OS Storage	100 GB
Hypervisor	VMware ESXi 5.5, 6.0, 6.5, 6.7
Supported Browsers ²	Chrome 79, Firefox ESR 68

1. The host CPUs must support the POPCNT CPU instructions (the Nehalem generation of Xeon CPUs (or later).
2. Internet Explorer is not supported. Other versions or browsers may or may not be compatible.
3. Refer to Installation Guide for additional details and recommendations.

About Riverbed

Riverbed enables organizations to maximize performance and visibility for networks and applications, so they can overcome complexity and fully capitalize on their digital and cloud investments. The Riverbed Network and Application Performance Platform enables organizations to visualize, optimize, remediate and accelerate the performance of any network for any application. The platform addresses performance and visibility holistically with best-in-class WAN optimization, network performance management (NPM), application acceleration (including Office 365, SaaS, client and cloud acceleration), and enterprise-grade SD-WAN. Riverbed's 30,000+ customers include 99% of the *Fortune* 100. Learn more at riverbed.com.

